

[May-2018-New100% Valid 200-601 PDF and VCE Dumps 90Q Provided by Braindump2go[68-78

2018 May New Cisco 200-601 Exam Dumps with PDF and VCE Just Updated Today! Following are some new 200-601 Real Exam Questions: 1. |2018 Latest 200-601 Exam Dumps (PDF & VCE) 90Q Download:

<https://www.braindump2go.com/200-601.html> 2. |2018 Latest 200-601 Exam Questions & Answers Download:

<https://drive.google.com/drive/folders/0B75b5xYLjSSNWTIxdF9WZmZqMms?usp=sharing> QUESTION 68 After commissioning several Stratix 5700 switches in a ring topology, you want to verify the installation against the network logical design. Specifically, you want to verify where the IGMP querier resides. What command can be issued in CLI to display the IP of the querier per VLAN? A. switch# show ip igmp snooping querier B. switch# show igmp snooping querier C. switch# show igmp querier D. switch# show ip igmp querier

Answer: A QUESTION 69 Which in-depth approach is used when deploying defense in an industrial zone? A. Use PLCs and control systems from multiple vendors in such a way that the process will become resilient for failures of one vendor. B. Deploy two factor authentications for all operators which need to login remote while working from home. C. Collect log files at a central location for easy back-up and encryption to provide privacy. D. Create multiple zones in the industrial zone and protect / inspect traffic between the zones with firewalls and intrusion monitors.

Answer: D QUESTION 70 How are I/O timeout and Safety I/O timeout calculated? A. An I/O connection will timeout based on the lower of 4x RPI or 100ms. Safety I/O timeout is calculated as 4xRPI. B. An I/O connection will timeout based on the lower of 3x RPI or 100ms. Safety I/O timeout is calculated as 3xRPI. C. An I/O connection will timeout based on the lower of 4x RPI or 150ms. Safety I/O timeout is calculated as 2xRPI. D. An I/O connection will timeout based on the lower of 3x RPI or 150ms. Safety I/O timeout is calculated as 3xRPI.

Answer: A QUESTION 71 Refer to the exhibit. CCNA.com has the industrial network shown in the exhibit. All switches are configured as layer 2 switches and are using VLAN 1 as their management VLAN. Each VLAN 1 interface has been assigned the correct IP address. What is the purpose of assigning a default gateway to SW-C switch? A. allows connectivity between the VLAN 1 interface on SW-C and other devices in the network. B. allows connectivity between Host A and other devices in the network. C. allows connectivity between Host B and other devices in the network. D. allows the switch to pass traffic between Host A and Host B

Answer: A QUESTION 72 Refer to the exhibit. Host 3 on Network A is sending data to Host 8 on Network B. Which address is the default gateway of Host 3? A. the address of the switch interface that is connected to router interface Fa0/0B. the address of the switch interface that is connected to router interface Fa0/1C. the address of the host that is connected to Network AD. the address of the host that is connected to Network BE. the address of the router interface Fa0/0F. the address of the router interface Fa0/1

Answer: E QUESTION 73 What are the two most relevant factors in determining the class of administration that is required to maintain the telecommunications infrastructure? (Choose two.) A. the size of the infrastructure B. the complexity of the infrastructure C. the age of the infrastructure D. the industry that the infrastructure supports E. the physical environment of the infrastructure

Answer: AB QUESTION 74 Which two ports does EtherNet/IP use to communicate? (Choose two.) A. TCP 44818B. UDP 44818C. TCP 502D. UDP 502E. TCP 2222F. UDP 2222

Answer: AF QUESTION 75 Which of the following correctly pairs the dotted decimal subnet mask with the correct number of binary bits that represent the subnet mask? A. 255.255.255.192 and /25B. 255.255.255.248 and /28C. 255.255.255.224 and /26D. 255.255.255.248 and /27E. 255.255.255.240 and /28F. 255.255.255.240 and /16

Answer: E QUESTION 76 Refer to the exhibit. What are three traffic and interconnection requirements for the devices in the exhibit? (Choose three.) A. The EtherNet/IP drive connections are in a high-voltage area and need protection from electromagnetic noise, so shielded cable that is rated for 600 V is advised. B. EtherNet/IP devices such as the controller, drive, VoIP phone, and IP camera should be in the same VLAN. C. CIP traffic has the highest bandwidth requirement so it needs the highest QoS setting. D. EtherNet/IP drive traffic has high sensitivity to random drops, latency, and jitter. E. Real-time motion control and VoIP traffic can share the same VLAN with the proper QoS setting. F. IEEE1588 and PTP are important for ensuring real-time synchronization.

Answer: ADF QUESTION 77 You are called upon to troubleshoot connectivity problems to a network device on a production floor. You have used ping and traceroute to verify that you cannot connect to the device from the management network. The network is 209.165.202.128/27 and the device has been given the IP address 209.165.202.158 and mask 255.255.255.224. You have verified that you can reach the device with your computer connected to the same switch as the device. What could be the cause of this problem? A. The device is set to the wrong subnet mask. B. The device is set to the wrong IP address. C. The device has no IP default gateway. D. The device is connected to a switchport in the wrong VLAN.

Answer: C QUESTION 78 Which prompt is used to configure parameters for the Ethernet ports of an industrial switch? A. Switch(config-if)# B. Switch(config-if-ind)# C. Switch(config-line)# D. Switch(config-ind)# E. Switch(config-vlan)#

Answer: A !!!RECOMMEND!!! 1. |2018 Latest 200-601 Exam Dumps (PDF & VCE) 90Q Download:

<https://www.braindump2go.com/200-601.html2>.|2018 Latest 200-601 Study Guide Video: YouTube Video:
[YouTube.com/watch?v=07100ZztBOA](https://www.youtube.com/watch?v=07100ZztBOA)